PRODUCT SHEET

HiiGARD Single Energy-Absorbing Lanyard, Scaffold Hook

HIIGARD COMPLIES WITH CSA Z259.11-17

DESCRIPTION

HiiGARD single lanyard in industrial-grade polyester, with an energy absorber, a small standard steel hook and a steel scaffold hook at the other end. Compliant with CSA Z259.11-17. Available in 4 ft and 6 ft.



- Small standard steel hook on the energy absorber end
- Steel scaffold hook at the other end
- Hook gate opening of 21 mm (5/8 in)
- Webbing width of 28 mm (1 1/10 in)
- Capacity of 68.1 to 140 kg (150 to 310 lb)
- Maximum absorber deployment of 1.35 m (4 ft 5 in)
- Protective sheath for labels
- Industrial-grade polyester material
- Black colour
- Available in 1.2 m (4 ft) and 1.8 m (6 ft) lengths

BENEFITS

- Built for tubular structures, direct connection with no accessory
- Proven durability on construction sites
- Regulatory labels protected from wear
- Recommended for workers connecting to scaffolding or tubular elements

Reference	Length m (ft-in)	Minimum capacity kg (lb)	Maximum capacity kg (lb)
HG-1540CLSL/4	1.2 (3' 11")	68.1 (150)	140 (309)
HG-1540CLSL/6	1.8 (5' 11")	68.1 (150)	140 (309)